

Part Number: 9773

Audio, Control & Instrument, #18-3pr, PO, Individ. Foil, PVC Jkt, CM



Product Description

Audio, Control & Instrument Cable, 18 AWG stranded (19x30) tinned copper conductors, polypropylene insulation, twisted pairs, individually shielded with Beldfoil® (100% coverage), 20 AWG stranded tinned copper drain wire, PVC jacket.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors	No. of Pairs
18	19x30	TC - Tinned Copper	6	3

Conductor Count:	6
Total Number of Pairs:	3
Conductor Size:	18 AWG

Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.019 in

Color Chart

Number	Color
1	Black & Red
2	Black & White
3	Black & Green

Color Chart 2

Number
17

Inner Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	20	Stranded mm

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.404 in	0.035 in

Electrical Characteristics

Conductor DCR

Individual Pair Nominal Shield DCR	Nominal Conductor DCR
8.3 Ohm/1000ft	6.4 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
30 pF/ft	55 pF/ft

Shielding:	Individually Foiled + No Overall
------------	----------------------------------

Inductance

Nominal Inductance

0.18 µH/ft

Impedance**Nominal Characteristic Impedance**

50 Ohm

Delay**Max. Delay Skew** | **Nominal Velocity of Propagation (VP) [%]**

66 ns/100m | 66 %

Current**Max. Recommended Current [A]**

Per conductor @ 25°C: 3.6 A

Current Table Note: 10C Temperature Rise

Voltage**UL Description** | **UL Voltage Rating**

UL AWM Style 2919 | Type CM: 300 V RMS

CM | 30 V RMS (UL AWM 2919)

Temperature Range

UL Temp Rating: 80°C (UL AWM Style 2919)

Operating Temp Range: -20°C To +80°C

Mechanical Characteristics

Bulk Cable Weight: 84 lbs/1000ft

Max Recommended Pulling Tension: 177 lbs

Min Bend Radius/Minor Axis: 4.25 in

Standards

NEC Articles: 800

NEC/(UL) Specification: CM

CEC/C(UL) Specification: CM

UL AWM Style: 2919 (30 V 80°C)

CPR Euroclass: Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/96/EC (BFR): Yes

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2012/19/EU (WEEE): Yes

EU Directive 2015/863/EU: Yes

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU CE Mark: Yes

EU RoHS Compliance Date (yyyy-mm-dd): 2004-01-01

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Suitability

Suitability - Indoor: Yes

Flammability, LSOH, Toxicity Testing

UL Flammability: UL1685 UL Loading

CSA Flammability: FT1

UL voltage rating: 300 V RMS (CM)

Plenum/Non-Plenum

Plenum (Y/N): N

Part Number

Variants

Item #	Color	Footnote
9773 060100	Chrome	
9773 0601000	Chrome	C
9773 060500	Chrome	C
9773 0605000	Chrome	C

Footnote:

C - CRATE REEL PUT-UP.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.