



## Part Number: H121A01

### COAX H121 AL PE CATV

#### Product Description

COAX [0.8/3.5] H121 AL PE CATV

#### Technical Specifications

##### Product Overview

Environmental Space:	Outdoor
Suitable Applications:	Coaxial cables used in cabled distribution networks designed according the European Standard EN 50117-2-2 and EN 50117-2-5; Operating at frequencies between 5 MHz and 3000 MHz

##### Physical Characteristics (Overall)

###### Conductor

AWG	Stranding	Material	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
21	Solid	BC - Bare Copper	0.8 mm	0.015 mm	1

Conductor Count:	1
------------------	---

###### Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	FPE - Foamed Polyethylene	3.5 mm	0.15 mm

###### Outer Shield Material

Type	Layer	Material	Coverage [%]	Min. Overlap	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Tape	1	Aluminum/Polyester/Aluminum		2 mm			
Braid	2	TC - Tinned Copper	37 %		4.1 mm	0.15 mm	4 %

###### Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PE - Polyethylene	5 mm	0.3 mm

OuterJacket1, Table Note:	According to European Standard HD 624
---------------------------	---------------------------------------

##### Construction and Dimensions

Min Elongation at Breakof Jacket:	300 %
Min Tensile Strength of Jacket:	10 MPa

##### Electrical Characteristics

###### Conductor DCR

Max. Conductor DCR	Max. Conductor Loop	Max. Shield DCR
35 Ohm/km	75 Ohm/1000ft	40 Ohm/km

###### Capacitance

Nom. Capacitance	Capacitance Tolerance
53 pF/m	2 pF/m

###### Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
----------------------------------	----------------------------------	-------------------------

75 Ohm	3 Ohm	Min. 40 dB
--------	-------	------------

#### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
5 MHz	2.3 dB/100m
50 MHz	5.9 dB/100m
100 MHz	8.1 dB/100m
230 MHz	12.1 dB/100m
400 MHz	15.9 dB/100m
800 MHz	22.7 dB/100m
862 MHz	23.6 dB/100m
1000 MHz	25.6 dB/100m
1350 MHz	30 dB/100m
1750 MHz	34.5 dB/100m
2150 MHz	39.6 dB/100m
2400 MHz	41 dB/100m
3000 MHz	45.9 dB/100m

#### Delay

Nominal Velocity of Propagation (VP) [%]	Velocity of Propagation Tolerance
84 %	2 %

#### High Freq

Frequency [MHz]	Min. RL (Return Loss) [dB]
5 - 30 MHz	20 dB
30 - 470 MHz	20 dB
470 - 1000 MHz	18 dB
1000 - 2000 MHz	16 dB
2000 - 3000 MHz	15 dB

High Freq Table Note:	In each frequency band, 3 peak values up to 4 dB lower are allowed
-----------------------	--

#### Screening

Frequency [MHz]	Min. Screening Attenuation	Min. Screening Attenuation After Flexing
30 - 1000 MHz	75 dB	
1000 - 2000 MHz		65 dB
2000 - 3000 MHz		55 dB

Screening Class:	C
------------------	---

#### Transfer Impedance

Frequency [MHz]	Transfer Impedance
5-30 MHz	Max. 50 mOhm/m

#### Voltage

Voltage Test Dielectric
2.0 kV DC

### Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-40°C To +70°C
Operating Temp Range:	-40°C To +70°C

### Mechanical Characteristics

Min Bend Radius (W/o Pulling Strength):	25 mm
Crush Resistance:	Max. 1% (load of 700N) N
Adhesion Dielectric:	6.3-63 N at 25 mm N

### Standards

CENELEC Compliance:	EN 50117-2-2, EN 50117-2-5 and EN 50117-1
RG Type:	59/U Type
Series Type:	Series 59

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01
---------------------------------------	------------

Part Number

Variants

Item #	Color	Length
H121A01.001000	Black	1,000 m
H121A01.00500	Black	500 m
H121A01.005000	Black	5,000 m
H121A01.00B100	Black	100 m

History

Update and Revision:	Revision Number: 0.151 Revision Date: 08-22-2019
----------------------	--

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.